



Elite

The ViewPlus Elite: larger-scale Production Braille embosser with high resolution Tactile Graphics

- The Elite is designed to fulfill high volume Braille production needs combined with high resolution tactile graphics
- Prints double-sided Braille in one pass, taking advantage of automatic print layout adjustments for enclosed tactile graphics
- The Elite uses continuous tractor feed paper up to 12-inch wide at a compact desktop machine size
- Provides a built-in **Ethernet** port for easy network installation

The **Braille dot** produced by ViewPlus embossers can be **adjusted in height**, allowing users to adjust to the individual sensibility of the reader's fingertip. This makes **extended Braille reading** more enjoyable, while maintaining **unsurpassed detail** in producing **tactile graphics**. The unique shape of the ViewPlus dot is proven to make Braille more durable, thus allowing **documents to last longer over time**.

ViewPlus solutions include **Windows printer drivers** that will allow embossing directly from Windows programs, utilizing the **same process as printing to mainstream color printers**. Additionally, direct printing from Braille note takers is also supported.

What you see on the screen is what ViewPlus embossers will print, **representing the color spectrum from white to black in 7 different heights of the embossed dots**.

The **Elite** is also available with **InkConnect**, which adds single-sided **black ink text and overprints on tactile graphics** to your Braille documents allowing sighted users to read along.

Though all ViewPlus embossers are compatible with other Braille translation software, like Duxbury, and RTFC, ViewPlus also offers the **Tiger Software Suite (TSS)** for Braille translation, tactile graphics design and more. TSS comes **FREE** with ViewPlus embossers and allows the user to create Braille documents in standard Windows programs such as MS Word and Excel without needing to know Braille.

For more information please contact info@cecitech.com or call 1800-304-1515
www.cecitech.com

Specifications:

Print Speed: Up to 200 CPS

Printing Mode: double sided

Braille Dot Heights:
Adjustable in 3 heights

Tactile Resolution: 20 DPI

Tactile Graphic Dot Heights:
7 steps for color representation

Paper: Continuous tractor feed

Paper Width: 4 - 12 in
(101 - 305 mm)

Paper Weight: 30 - 140 lb
(50 - 230 gsm)

Connection: USB, Ethernet

Compatibility: Current Windows
operating systems, Mac OS 10.9+

Height: 8.8 in (224 mm)

Width: 22.3 in (569 mm)

Depth: 13.8 in (351 mm)

Weight: 60 lbs (27,2 kg)

With InkConnect:

Height: 10.7 in (272 mm)

Depth: 14.6 in (524 mm)

Recommended Temperature:

55 - 95 °F (13 - 35 °C)

Storage Temperature:

-4 - 158 °F (-40 - 70 °C)

Humidity: 20 - 80% RH

(non-condensing)

Energy Supply: 85 - 264 VAC

50/60 Hz (+/- 3%)

Standby: 22 W

Heavy Embossing: 235 W

